

# **APE Single Acting Diesel Impact Hammer**

# THE WORLD'S LARGEST PILEDRIVERS

# **Model D100-42**

## SPECIFICATIONS

Stroke at Maximum Rated Energy Maximum Rated Energy (Setting 4) (Setting 3) (Setting 2) Minimum Rated Energy (Setting 1) (VARIABLE THROTTLE ALLOWS FOR INFINITE FUEL SETTING)

Maximum Obtainable Stroke Maximum Obtainable Energy Speed (Blows Per Minute)

#### WEIGHTS (APPROXIMATE)

Piston Anvil Anvil Cross Sectional Area Hammer Weight (Includes Trip Device) Typical Operating (Weight With Offshore Leader)

### CAPACITIES

Fuel Tank (Runs on Diesel or Bio-Diesel) Oil Tank

#### CONSUMPTION

Diesel or Bio-Diesel Oil Tank Grease

#### STRIKER PLATE

Weight Diameter Area Thickness

### CUSHION MATERIAL

Type/Qty Diameter-DB32 Thickness

Type/Qty Thickness Diameter Total Combined Thickness Area Elastic-Modulus Coeff. of Restitution

#### STANDARD OFFSHORE LEADER

8 in x 54 in for 48 in Piles and Under

MINIMUM BOX LEAD SIZE / OPERATING LENGTH Minimum Box Leader Size Operating Length as Described above

135 in (343 cm) 248,063 ft-lbs (336.31 kNm) 205,892 ft-lbs (279.14 kNm) 163,721 ft-lbs (221.96 kNm) 121,551 ft-lbs (164.79 kNm)

150 in (381 cm) 275,625 ft-lbs (373.68 kNm) 34-53

22,047 lbs (10,000 kg) 4,670 lbs (2,118 kg) 482.8 in<sup>2</sup> (3,114.83 cm<sup>2</sup>) 47,000 lbs (21,318 kg) Consult Factory

40.3 Gal (153 Liters) 8.3 Gal (31.4 Liters)

7.8 Gal/hr (29.5 Liters/hr) 0.67 Gal/hr (2.5 Liters/hr) 8 to 10 Pumps Every 20 Minutes of Operation Time.

> 1,036 lbs (470 kg) 25 in (63.5 cm) 491 in<sup>2</sup> (3,167.74 cm<sup>2</sup>) 8 in (20.32 cm)

Micarata / 2 each 25 in (63.5 cm) 1 in (2.54 cm)

Aluminum / 3 each 1/2 in (1.27 cm) 25 in (63.5 cm) 3.5 in (8.89 cm) 491 in2 (3,167.74 cm2) 285 ksi (1,965 mpa) 0.8

Consult Factory

8 in x 37 in (20.32 cm x 94 cm) 396 in (1,005.84 cm)



Optional Variable Throttle Control





MC 904 6" Well Stack up

NTION







opyright © 2022 American Piledriving Equipment Inc. All Rights F

Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice. Consult the factory for details on any specific product (800) 248-8498.

WWW.AMERICANPILEDRIVING.COM Ape@americanpiledriving.com