

APE Model D80-23 Single Acting Impact Hammer

operates on diesel or bio-diesel for all types of impact pile driving



MODEL D80-23 (8.0 metric ton ram)

SPECIFICATIONS

Maximum rated energy	202,825 ft/lbs (274,993 Nm)
Minimum rated energy	126,192 ft/lbs (171,093 Nm)
Stroke at rated energy	11.5 ft (3.5 m)
Maximum obtainable stroke	14.82 ft (4.52 m)
Speed (blows per minute)	36-45

WEIGHTS (Approximate)

Ram	17,637 lbs (8,000 kg)
Anvil	5,004 lbs (2,270 kg)
Hammer weight (includes trip device)	37,269 lbs (16,905 kg)
Typical operating weight w/ guides & drive cap	Varies- consult factory

CAPACITIES

Fuel tank (runs on diesel or bio-diesel)	40.94 gal (155 liter)
Oil tank	8.45gal (32 liter)

CONSUMPTION

Diesel or Bio-diesel fuel	6.6 gal/hour (25 liter/hr)
Lubrication oil	.77 gal/hour (2.9 liter/hr)
Grease	twice per day

DIMENSIONS OF HAMMER

a	Length overall	244 in (6,200 mm)
a	Length over cylinder extension	283 in (7,190 mm)
a	Length over trip tubes	343 in (8,712 mm)
b	Impact block diameter	32.28 in (820 mm)
c	Width over bolts	43.7 in (1,110 mm)
d	Hammer width overall	35 in (889 mm)
e	Width for guiding- face to face	31.5 in (800 mm)
f	Hammer center to pump guard	21.57 in (548 mm)
g	Hammer center to bolt center	13.78 in (350 mm)
h	Hammer depth overall	43.7 in (1,110 mm)
H	Minimum clearance for leads	26 in (660 mm)

APE D80-23 can be used in 37 inch US Style box leads.

APE also provides off shore type leads and bottom drive type leaders for super large diameter piles and caissons.

Features

- Fuel injection designed by APE engineers*
- Hardened piston needs no high maintenance wear rings*
- Optional direct drive for high speed production on steel piles*
- Fuel pump mounted where heat will not harm it*
- Variable mechanical cam fuel pump- no air pistons or rings*
- Optional hydraulic variable fuel remote control*
- Heavy duty trip system for years of fault free operation*
- Chrome rings for super long life*
- Low maintenance and extremely low parts pricing*
- German design at a reasonable price*
- Two year APE warranty*



Corporate Offices
7032 South 196th
Kent, Washington 98032 USA
(800) 248-8498 & (253) 872-0141
(253) 872-8710 Fax

Visit our WEB site:
www.apevibro.com
e-mail: ape@apevibro.com