



# APE Single Acting Diesel Impact Hammer

## THE WORLD'S LARGEST PILEDRIVERS

## Model D36-52

### SPECIFICATIONS

Stroke at Maximum Rated Energy	135 in (343 cm)
Maximum Rated Energy (Setting 4)	89,303 ft-lbs (121.07 kNm)
(Setting 3)	74,121 ft-lbs (100.49 kNm)
(Setting 2)	58,940 ft-lbs (79.91 kNm)
Minimum Rated Energy (Setting 1)	43,758 ft-lbs (59.33 kNm)
(VARIABLE THROTTLE ALLOWS FOR INFINITE FUEL SETTING)	
Maximum Obtainable Stroke	150 in (381 cm)
Maximum Obtainable Energy	99,225 ft-lbs (134.52 kNm)
Speed (Blows Per Minute)	34-53

### WEIGHTS (APPROXIMATE)

Piston	7,937 lbs (3,600 kg)
Anvil	1,358 lbs (616 kg)
Anvil Cross Sectional Area	367.94 in <sup>2</sup> (2,373.80 cm <sup>2</sup> )
Hammer Weight (Includes Trip Device)	22,795 lbs (10,340 kg)
Typical Operating (Weight With DB32 & H-Beam insert)	28,097 lbs (12,745 kg)

### CAPACITIES

Fuel Tank (Runs on Diesel or Bio-Diesel)	17.70 Gal (67 Liters)
Lubrication Oil Tank	5.02 Gal (19 Liters)

### CONSUMPTION

Diesel or Bio-Diesel	3.31 Gal/hr (12.54 Liters/hr)
Lubrication Oil Tank	.53 Gal/hr (2 Liters/hr)
Grease	8 to 10 Pumps Every 20 Minutes of Operation Time.

### STRIKER PLATE FOR DB32

Weight	1,036 lbs (470 kg)
Diameter	25 in (63.5 cm)
Area	491 in <sup>2</sup> (3,167.74 cm <sup>2</sup> )
Thickness	8 in (20.32 cm)

### CUSHION MATERIAL

Type/Qty	Micarata / 2 each
Diameter-DB32	25 in (63.5 cm)
Thickness	1 in (2.54 cm)
Type/Qty	Aluminum / 3 each
Thickness	1/2 in (1.27 cm)
Diameter	25 in (63.5 cm)
Total Combined Thickness	3.5 in (8.89 cm)
Area	491 in <sup>2</sup> (3,167.74 cm <sup>2</sup> )
Elastic-Modulus	285 ksi (1,965 mpa)
Coeff. of Restitution	0.8

### DRIVE CAP

DB 32:	2,436 lbs (1,105 kg)
--------	----------------------

### INSERT WEIGHT

H-Beam Insert for 12" (305mm) and 14" (355 mm):	948 lbs (430 kg)
Large Pipe Insert for the Sizes 12" to 24" Diameter:	1,830 lbs (830 kg)


### MINIMUM LEADER SIZE/OPERATING LENGTH

Minimum Box Leader Size	8 in x 32 in (20.32 cm x 81.28 cm)
Operating Length with Base and Insert	354 in (900 cm)




Image may not represent actual Model

Optional Variable Throttle Control



Drive Base Assembly



Striker plate

Aluminum

Micarta

Aluminum

Drive Cap Base



Specifications may vary due to site conditions, specific hammer conditions or product set up.

Specifications may change without notice.

Consult the factory for details on any specific product (800) 248-8498.

Copyright © 2022 American Piledriving Equipment Inc. All Rights Reserved



WWW.AMERICANPILEDIVING.COM

Ape@americanpiledriving.com